



AXIS OfficeBasic USB Network Print Server

Sharing printers has never been easier...

Combining unique multi-language support and automatic installation, the AXIS OfficeBasic USB print server is the user-oriented network print server for small offices and local networks.

With support for Windows and AppleTalk networks, the AXIS OfficeBasic USB is the perfect solution for sharing any USB printer in PC and Mac environments. Just plug and print!

Good value today... and tomorrow!

With over 18 years experience of innovative printing excellence, Axis now have over 2.5 million network print servers installed. With a keen awareness for technological change and an aggressive approach to product development, Axis encourage customers to keep pace with the very latest printer developments with free firmware upgrades published regularly over the Web. By offering cutting-edge, future-proof technology, Axis' print server products continue to represent good value today... and tomorrow!

You'll find Axis' unique network technology and customer-oriented approach to design clearly evident in this intuitive, easy-to-use print server that boasts:



- Windows and Appletalk support for 10/100baseT Ethernet networks
- Intuitive Web-based interfaces in English, French, German, Italian and Spanish
- Automatic print server discovery and IP address assignment
- Special mounting kit for convenient positioning, allows you to design your print area exactly the way you want it

AXIS OfficeBasic USB Print Server

Supported Printers

- USB 1.1 & 2.0 printers from e.g. Brother, Canon, Epson, HP, IBM, Lexmark, Minolta, OKI and Xerox running PCL, PS, LX, LQ, IBM proprinter and other similar languages

Supported Systems

- Microsoft Windows: Windows 98, Me, NT4, 2000 and XP.
Print Methods: NetBEUI, LPR, Raw TCP
- Apple EtherTalk: Macintoshes System 7, PowerMac, PowerMac G3/G4, MacOS X version 10.X.
Print Methods: AppleTalk and LPR
- WWW: Netscape 4.76 or higher and MS Internet Explorer 4.x or higher

Supported Protocols

- Windows: NetBIOS/NetBEUI, RawTCP, LPR, IPP, WINS, ARP, DHCP, DNS, DDNS, SNMP, SLP
- TCP/IP: ARP, DHCP, BOOTP, RARP, DNS, DDNS, FTP, LPR, Reverse Telnet, PROS, IP, TCP, UDP, HTTP, SLP, ICMP, IGMP, SNMP
- Apple EtherTalk: AAPR, ATP, DDP, NBP, PAP, RTMP, ZIP

Supported Languages

- English, French, German, Italian, Spanish

Print Server Management

- Embedded web pages for product configuration, management and monitoring

Logical Connection

- Ethernet: Use of IEEE802.2, IEEE802.3, SNAP and Ethernet II frame types simultaneously
- Fast Ethernet: Supports NWay that provides auto-detection of network speed. Use of IEEE802.2, IEEE802.3, SNAP and Ethernet II frame types simultaneously, full duplex

Network Attachments

- Ethernet: RJ-45 connector (Category 5 shielded twisted pair cable) for 10baseT Ethernet or 100base TX

USB Port

- USB 1.1 Low and Full speed. Tested with USB 2.0 printers

Power Consumption

- Power provided by external supply. Maximum 5.6W (Type PS-H, 5.1 VDC 2000mA)

Dimensions

- Height: 2.9 cm/1.1 in, Width 6.2 cm/2.4 in, Depth 13.0 cm/5.1 in, Weight 0.077 kg/0.17 lb

Environmental

- Temperature: 40-105 °F (5-40 °C),

Approvals

- EMC: EN 55022/1998, EN 55024:1998, EN 61000-3-2, EN 61000-3-3, VCCI Class B, C-TICK AS/NZS 3548, Compliance to FCC part 15 Subpart B, Class B
- Safety: EN 60950

Hardware

- 32-bit 100 MHz RISC Controller, 2 MB Flash memory, 8 MB RAM



Front Panel

- 2 LED indicators: Power and Network
- Test button for information printouts

Included Accessories

- AXIS Network Product CD containing printing and installation tools including AXIS IP Jumpstarter
- Wall mounting clip
- USB cable



More information: www.axis.com