

AXIS OfficeBasic Network Print Server

Sharing printers has never been easier

Combining unique multilingual support and automatic installation, the AXIS OfficeBasic print server is the user-oriented network print server for small offices and local networks.

With support for Windows and MacOS networks, AXIS OfficeBasic is the perfect solution for sharing any USB or parallel printer in PC and Mac environments. Just plug and print!

Good value today...and tomorrow!

With over 20 years experience of innovative printing excellence, Axis now has over 3 million network print servers installed. With a keen awareness for technological change, Axis encourages customers to keep pace with the very latest printer developments with free firmware upgrades published regularly over the web. By offering cutting-edge, future-proof technology, Axis' print server products continue to represent good value today...and tomorrow!

You'll find Axis' unique network technology and customer-oriented approach to design clearly evident in this intuitive, easy-to-use print server.



- Quick and easy installation
- Easy web-based management
- Superior reliability
- Multilingual support



Specifications			
Supported printers	USB 1.1, USB 2.0 and parallel printers from e.g. Brother, Canon, Epson, HP, IBM, Lexmark, Minolta, OKI and Xerox running PCL, PS, LX, LQ, IBM proprinter and othe similar languages.*	Installation management and maintenance	Embedded web pages for product configuration, management and monitoring
Front panel	2 LED indicators: Power and Network Test button for information printouts	Supported systems	Microsoft Windows: 2000/XP/2003 Apple EtherTalk: Macintosh System 7, 8, 9 MacOS X version 10.X
Network connection	Ethernet: RJ-45 connector (Category 5 shielded twisted pair cable) for 10baseT Ethernet or 100base TX	Supported web browsers	Any standard web browser (MS Internet Explorer 5.x or higher, Netscape 6.0 or higher)
Printer connection	USB 1.1 Low and Full speed. Tested with USB 2.0 printers. 36-Pin centronics connector parallel port, high speed IEEE 1284 compliant. Including ECP support	Supported languages	English, French, German, Italian, Japanese and Spanish
Logical connection	Ethernet: Use of IEEE802.2, IEEE802.3, SNAP and Ethernet II frame types simultaneously Fast Ethernet: Supports NWay that provides auto-detection of network speed. Use of IEEE802.2, IEEE802.3, SNAP and Ethernet II frame types simultaneously, full duplex	Supported protocols	Windows: NetBIOS/NetBEUI, RawTCP, LPR, WINS, ARP, DHCP, DNS, DDNS, SNMP, SLP TCP/IP: ARP, DHCP, BOOTP, RARP, DNS, DDNS, FTP, LPR, Reverse Telnet, IP, TCP, UDP, HTTP, SLP, ICMP, IGMP, SNMP Apple EtherTalk: AAPR, ATP, DDP, NBP, PAP, RTMP, ZIP
Processors and memory	32-bit 100 MHz RISC Controller RAM: 8 MB, Flash: 2 MB	Included accessories	AXIS Network Product CD containing printing and installation tools including AXIS AddPrinter Wall mounting clip USB cable
Power	Power provided by external supply Maximum 5.6 W (Type PS-H, 5.1 VDC 2000mA)	Approvals	EMC: EN 55022/1998, EN 55024:1998, EN 61000-3-2, EN 61000-3-3, VCCI Class B, C-TICK AS/NZS CISPR 22, Compliance to FCC part 15 Subpart B, Class B Safety: EN 60950
Operating conditions	Temperature: 5-40 °C (40-105 °F)	Dimensions (HxWxD) and weight	29 x 62 x 117 mm (1 1/8" X 2 13/32" X 4 19/32") 81 g (2 7/8 oz)

*Exception: PPA, CAPT, GDI and other host-based printers are not supported.

www.axis.com